

PATINA Translucent Fabric

Specifications

Product Type: Interior
 Composition: 100% Polyester
 Roll Width: 110"
 Thickness: .018 in
 Mesh Weight: 8.1 oz/yd²
 Openness Factor: Approximately 1%
 UV Blockage: Approximately 88-99%; varies by color

Color	TS	RS	AS	TV	RV	AV	SC	Total g value
Bamboo	28	38	34	26	37	37	0.63	0.37
Birch	20	34	46	17	31	52	0.67	0.32
Jasper	3	13	84	2	12	86	0.87	0.24
Hazel	12	24	64	8	20	72	0.77	0.29

TS= Solar Transmittance
 RS= Solar Reflectance
 AS= Solar Absorption
 TV= Visual Transmittance
 RV= Visual Reflectance
 AV= Visual Absorption
 SC= Shading Coefficient

1/4CL= 1/4" Clear Glass
 1CL- 1" Insulating Clear Glass
 1/4HA= 1/4" Heat Absorbing Glass
 1HA= 1" Insulating Heat Absorbing Glass

The solar optical properties are used to calculate the shading coefficient. The shading coefficient represents the percentage of solar heat gain that is transmitted to the interior through the glass and shading system combined. Darker colors provide maximum glare reduction and visibility.