



## Sierra Solar Screen Fabric Product Specifications

**Benefits:** Sierra solar screen fabric offers value and performance in 5 color choices to complement any décor. Woven in a 2 x 2 basketweave pattern to maximize clarity of view.

### Specifications

<b>Category</b>	Solar Screen Fabric	<b>Composition</b>	24% Polyester
<b>Openness Factor</b>	3% & 5%		76% PVC
<b>UV Blockage</b>	Approximately 95-97%	<b>Thickness</b>	0.024" (0.55 mm) ±5%
<b>Weave style</b>	2 x 2 Basket weave	<b>Weight</b>	400 g/m2
		<b>Width</b>	118" ( 300 cm) ±50 mm)

<b>Fire Classifications:</b>	NFPA 701
<b>Anti-Microbial Properties:</b>	ASTM-G21
<b>Certifications:</b>	GreenGuard Gold Confidence in Textiles Oko-Tex
<b>Environmental Benefits:</b>	RoHS- Lead Free
<b>Care &amp; Cleaning:</b>	Dust removal with vacuum (soft dusting brush), compressed air, or soft brushing. Do not scrub, wipe clean with sponge using clean water.

For complete technical information, current test results, performance specifications and larger samples, contact the Insolroll, Inc.

### Fenestration Properties

(Solar Optical Properties)

Fabrics installed internally,  
Zero-degree profile

#### 1% open colors

Color	Ts	RS	AS	TV	SHGC*
White/White	22	70	8	19	0.27
White/Grey	12	49	39	9	0.32
White/Linen	17	57	26	13	0.3
Charcoal/Bronze	5	9	86	7	0.43
Black/Black	3	4	93	5	0.44
Black/Dark Grey	1	11	88	2	0.48

#### 3% open colors

White/White	22	70	8	19	0.27
White/Grey	12	49	39	9	0.32
White/Linen	17	57	26	13	0.3
Charcoal/Bronze	5	9	86	7	0.43
Black/Black	3	4	93	5	0.44
Black/Dark Grey	4	12	84	5	0.48

#### 5% open colors

White/White	25	67	7	22	0.29
White/Grey	14	49	37	11	0.32
White/Linen	19	57	24	15	0.3
Charcoal/Bronze	7	8	85	10	0.44
Black/Black	5	4	91	8	0.44

**Definition of terms:**

<b>Ts</b> = Solar Transmittance	Energy that is allowed to pass through
<b>Rs</b> = Solar Reflectance	Energy that is reflected away
<b>As</b> = Solar Absorptance	Energy that is absorbed by the fabric
<b>Tv</b> = Visible Light Transmission	Percentage of visible light that comes into the room
<b>OF</b> = Openness Factor	Percentage of fabric that is open (between the threads)
<b>SHGC</b> = Solar Heat Gain Coefficient	The percentage of incident solar radiation that is transmitted as heat to the interior through the glass and shading system*.
<b>CL</b> = Clear Glass	

\*Glass tested: 1/4" Heat Absorbing. SHGC was calculated by multiplying SC (Shading Coefficient provided by mill) by 0.87.

**Insolroll Window Shading Systems** | 637 S. Pierce Ave. | Louisville, CO | 80027  
tel 800.447.5534 | [www.insolroll.com](http://www.insolroll.com) | [info@insolroll.com](mailto:info@insolroll.com)

©2016