

INSOLROLL ELEMENTS® **Finale Blackout Fabric**
 Product Specifications

Benefits: Finale blackout fabric is paired with Interlude translucent fabric to feature the same texture and color selections for total light and privacy management throughout the home. With its rib weave in varied weft colors, this fabric pair's soft, heathered texture evokes warmth and depth and adds dimension to any room.

Specifications:			
Category	Blackout Fabric	Composition	100% Polyester
Openness Factor	0%	Thickness	0.018"
UV Blockage	100%	Weight	8.8 oz/yd ²
		Width	94"

Certifications:	GreenGuard Oeko-Tex Standard 100 REACH Compliant
------------------------	--

Care & Cleaning: Remove dust with a vacuum cleaner or compressed air. Clean with a sponge and warm soapy water using mild detergent. Rinse with clean water. Do not scrub. Do not use solvents or abrasives that could harm the coating of the fabric. Leave the blind down until completely dry. You may also very gently rub the fabric with a clean white pencil eraser to remove small stains.

For complete technical information, current test results, performance specifications and larger samples, contact the Insolroll, Inc.

Fenestration Properties:		Definition of terms:	
(Solar Optical Properties)			
Fabrics installed internally, Zero-degree profile			
Blackout colors			
Color	Ts RS AS TV SHGC*	Ts = Solar Transmittance	Energy that is allowed to pass through
Chestnut	0 70 30 0 0.33	Rs = Solar Reflectance	Energy that is reflected away
Natural White	0 70 30 0 0.33	As = Solar Absorptance	Energy that is absorbed by the fabric
Nordic Coal	0 65 35 0 0.35	Tv = Visible Light Transmission	Percentage of visible light that comes into the room
Silver Dust	0 70 30 0 0.33	OF = Openness Factor	Percentage of fabric that is open (between the threads)
Warm Almond	0 67 33 0 0.34	SHGC = Solar Heat Gain Coefficient	The percentage of incident solar radiation that is transmitted as heat to the interior through the glass and shading system*
Wood Smoke	0 71 29 0 0.33	CL = Clear Glass	
		*Glass tested: 1/4" Heat Absorbing. SHGC was calculated by multiplying SC (Shading Coefficient provided by mill) by 0.87.	
		The solar optical properties are used to calculate the shading coefficient. The shading coefficient represents the percentage of solar heat gain that is transmitted to the interior through the glass and shading system. Darker Colors provide maximum glare reduction and visibility.	