

Product Specifications

Benefits: Interlude translucent fabric is paired with Finale blackout fabric to feature the same texture and color selections for total light

and privacy management throughout the home. With its rib weave in varied weft colors, this fabric pair's soft, heathered

texture evokes warmth and depth and adds dimension to any room.

Specifications:

Category Composition Translucent Fabric 100% Polyester **Thickness Openness Factor** 0% 0.013" **UV Blockage** 100% Weight 4.6 oz/yd2 Width 94"

Certifications: GreenGuard Gold

Oeko-Tex Standard 100

REACH Compliant

Care & Cleaning: May be dusted with a damp cloth. When scrubbing is necessary, warm water, mild detergents, and gentle rubbing are

For complete technical information, current test results, performance specifications and larger samples, contact the Insolroll, Inc.

Fenestration Properties: Fabrics installed internally,				nternall	у,	Definition of terms:	
(Solar Optical Properties) Zero-degree profile				file			
Translucent Colors						Ts = Solar Transmittance	Energy that is allowed to pass through
Color	Ts	RS	AS	TV SHGC*		Rs = Solar Reflectance	Energy that is reflected away
Chestnut	6	65	29	4	0.35	As = Solar Absorptance	Energy that is absorbed by the fabric
Natural White	21	69	10	20	0.34	Tv = Visible Light Transmission	Percentage of visible light that comes into the room
Nordic Coal	3	61	36	3	0.36	OF = Openness Factor	Percentage of fabric that is open (between the threads)
Silver Dust	10	65	25	7	0.35	SHGC= Solar Heat Gain Coefficient	The percentage of incident solar radiation that is transmitted
Warm Almond	12	67	21	8	0.34		as heat to the interior through the glass and shading system*
Wood Smoke	4	61	35	3	0.36	CL = Clear Glass	
					*Glass tested: 1/4" Heat Absorbing. SHGC was calculated by multiplying SC (Shading Coefficient provided by mill) by 0.87.		
						The solar optical properties are used t	to calculate the shading coefficieint. The shading coefficient

Insolroll Window Shading Systems | 637 S. Pierce Ave. | Louisville, CO | 80027

©2023

and shading system. Darker Colors provide maximum glare reduction and visibility.

represents the percentage of solar heat gain that is transmitted to the interior through the glass

tel 303.665.1207 | www.insolroll.com