



Sundown Blackout Fabric Product Specifications

Benefits: Sundown blackout combines the functionality and durability of a typical solar screen with the light-blocking and privacy of a 100% blackout fabric. Its elegant matte finish brings an air of sophisticated serenity to any space. Unlike some blackout fabrics, is the same color on the outside as the inside. Perfect for bedrooms and enhanced media-viewing, Sundown is available in 7 neutral colors.

Specifications:

Category	Blackout Fabric	Composition	25% Polyester, 75% PVC
Openness Factor	0%; opaque	Thickness	0.027"
UV Blockage	~100%	Weight	16.96 oz/yd ²
		Width	118"
FR (Fire Rating)	NFPA 701		
Antimicrobial	ASTM G-21 and E-2180; also has Sanitized* Antimicrobial Treatment		

Environmental Benefits:

PVC-Free
Lead Free
Phthalate Free
Formaldehyde Free
UL GREENGUARD Gold Certified for low chemical emissions into indoor air during product usage.
Oeko-Tex® Standard 100 Certified- Free of harmful chemicals

Warranty

10 year manufacturer's warranty

Noise Reduction

NRC 0.1 SAA 0.11

Care & Cleaning:

Gently vacuum with soft brush attachment.

For complete technical information, current test results, performance specifications and larger samples, contact Insolroll, Inc.

Solar Optical Properties (Zero degree profile angle)					
	Fabric Performance				Fabric Plus Glass Performance
	T R A N S M I T T A N C E	R E F L E C T A N C E	A B S O R P T A N C E	T R A N S M I T T A N C E	S O L A R H E A T C O E F F I C I E N T
Color	Ts	Rs	As	Tv	SHGC
Ice	0.0	65.0	35.0	0.0	0.13
Barley	0.0	58.0	42.0	0.0	0.16
Pumice	0.0	50.0	50.0	0.0	0.2
Alloy	0.0	74.2	25.8	84.0	0.16
Shale	0.0	74.2	25.8	84.0	0.26
Graphite	0.0	74.2	25.8	84.0	0.33
Black	0.0	74.2	25.8	84.0	0.4

Insolroll Window Shading Systems | 637 S. Pierce Ave. | Louisville, CO | 80027
tel 303.665.1207 | www.insolroll.com

©2024

*The Sanitized® hygiene function is added to the fabric during manufacturing and protects the fabric surface from the formation of fungi (including mold and mildew) and bacterial odors, providing long lasting material protection.